



Arak Petrochemical Company



ISO 9001:2000

Certificate No.: CH98/8032

ISO 14001:2004

Certificate No.: CH03/0112

OHSAS 18001:1999

Certificate No.: CH05/0675

**Address:**

No. 3, Taban St.  
Vali-e-Asr Ave.  
Tehran - IRAN

**Tel:**

(+98 21)82122700

**Fax:**

(+98 21)8867 4126-27

**Web-site:**

www.arpc.ir

**E-mail:**

Sales@arpc-ir.net

## Polypropylene

### Moplen HP502N (Injection Moulding)

Typical properties	Test method (ASTM)	Unit	Value
MFR @230°C, 2.16 kg	D1238/L	gr/10min	12
Flexural Modulus	D790	Mpa	1400
Notched Izod Impact@23°C	D256	J/m	20
Tensile Strength@Yield	D638	Mpa	34
Elongation@Yield	D638	%	12
Vicat Softening Point, 10N	D1525	°C	154
HDT(0.46N/mm <sup>2</sup> )	D648	°C	95
Rockwell Hardness	D785	R.Scale	102
Oven Aging@150°C	D3012	Hours	360

➤ Values shown are averages & are not to be considered as product specifications.

#### ❖ Main application & Characteristics:

Moplen HP502N is a medium-high fluidity polypropylene homo-polymer for injection moulding. Because of its good flow properties; this grade offers easy mould filling & short cycle times. Articles produced from Moplen HP502N exhibit good dimensional stability & high stiffness.

Moplen HP502N is widely used for injection moulding consumer goods such as food containers, cool boxes, vacuum flasks, flower pots, toys, garden furniture & small appliances. In the medical sector Moplen HP502N is used for 3-part syringes & a wide range of health care items.

Other applications are closures, caps & crates for products.

\* Moplen HP502N is suitable for food contact.