



Arak Petrochemical Company



ISO 9001:2000

Certificate No.: CH98/8032

ISO 14001:2004

Certificate No.: CH03/0112

OHSAS 18001:1999

Certificate No.: CH05/0675

Address:

No. 3, Taban St.
Vali-e-Asr Ave.
Tehran - IRAN

Tel:

(+98 21)82122700

Fax:

(+98 21)8867 4126-27

Web-site:

www.arpc.ir

E-mail:

Sales@arpc-ir.net

Linear Low Density Polyethylene

BD24250AA

Typical properties	Test method (ASTM)	Unit	Value
MFI@190°C, 2.16 kg	D1238	gr/10min	25
Density	D2839	gr/ml	0.924
Flexural Modulus	D790	Mpa	390
Notched Izod Impact@23°C	D256	J/m	25
Tensile Strength@Yield	D638	Mpa	13
Elongation@Break	D638	%	150

➤ Values shown are averages & are not to be considered as product specifications.

❖ Main application & Characteristics:

BD24250AA is a linear low density polyethylene copolymer containing butene-1 as a co-monomer.

BD24250AA is suitable for high flow injection moulding applications such as house wares, boxes and closures.

The superior stress crack resistance makes it particularly good for caps and closures.

* **BD24250AA** is suitable for food contact.